The

Technical Bulletins

of

Dianetics and Scientology

by

L. Ron Hubbard

FOUNDER OF DIANETICS AND SCIENTOLOGY

Volume

IV

1960-1961

HUBBARD COMMUNICATIONS OFFICE
Saint Hill Manor, East Grinstead, Sussex

HCO BULLETIN OF 9 FEBRUARY 1960

HCOs
Central Orgs Post
But not London
Paying Fran Holders Only

RESEARCH ADVANCES

I wish to thank all HCOs and Central Orgs outside the United Kingdom for their financial support of existing research lines.

Much of the research advances I have made in the last few months were possible because:

1. The increasing self-determinism of HCOs and Central Organizations, as attested by their increasing size and income, has freed me from much administrative labour and worry, thus giving me more research time, and

2. Increasing financial support from HCOs and Central Organizations as well as some Franchise Holders, while not yet furnishing me all the needed facilities, has made it possible for me to extend research lines further and faster than they otherwise would have gone and has reduced and lightened the labour involved.

I wish to thank in particular all HCO Secretaries, all heads of Central Orgs, all HCO and Central Organizations' staffs for the splendid work they are doing and for the mainstay of research support. And I wish to thank those Franchise Holders who have contributed regularly to research and who are expanding Scientology throughout the World.

We are starting *this* decade right!

L. RON HUBBARD

LRH:js.rd
Copyright © 1960
by L. Ron Hubbard
ALL RIGHTS RESERVED

HUBBARD COMMUNICATIONS OFFICE
Saint Hill Manor, East Grinstead, Sussex

HCO BULLETIN OF 10 FEBRUARY 1960

CenOCon
Place 1 in each
British E-Meter

BRITISH E-METER OPERATION

(see diagram on following page)

To operate the British version of the Electrometer designed under my guidance by Fowler and Allen, a British instrument firm, the following steps must be done at the beginning of each session.

The instrument has a 5,000 ohm calibration knob (a) and switch (b) not present on the U.S. Meter.

Before (or after) plugging in the electrodes at (e), with the tone arm at "off", throw the 5,000 ohm switch (b) downwards from "off". Then turn the instrument on with the tone arm (c) and place the tone arm at 2.

Now move the otherwise unmarked calibration knob (a) left or right until the needle is exactly on "set" on the dial.

Then move the tone arm to the white dot (g) between 2 and 3. The needle should move over to "test". If it does the batteries are properly up (they last a year or more unless you carelessly leave the meter "on" for days when not in use).

Now click the 5,000 ohm switch (b) up to "off".

Hand the pc the electrodes.

Have the pc squeeze the electrodes. The needle should fall 1/3 of the dial or more. Shift the 1—16 sensitivity arm (d) up or down until the pc, squeezing the cans, *does,* on one squeeze, get a 3rd of a dial drop.

You are now ready to audit.

Keep the needle around the "set" mark. Keep the sensitivity low so that you only get significant readings (not breath or heart beat). Most pcs run around 1 on sensitivity on this meter which is very live. Sticky pcs have to have a higher sensitivity setting.

When finished with the session and the meter, turn the tone arm to "off" or your battery will wear out much faster.

Stow the cord to the electrodes inside the electrodes which are hollow. A little examination will show you how. Then stow the electrodes in the case and close it.

Use the U.S. E-Meter book for all other meter particulars.

If your meter ceases to function ship to Fowler and Allen, 39 Mackenzie Rd, Beckenham, Kent, at your postage expense. Enclose return postage. Unless due to carelessness or breakage, they will service and re-battery your meter. Opening the panel or changing the meter about inside voids the guarantee.

LRH:js.rd L. RON HUBBARD

Copyright © 1960
by L. Ron Hubbard
ALL RIGHTS RESERVED